



# LED Bulb Replacement for Recessed Ceiling Lights

## True Value

10W 218-641

12W 218-642



Installation is as easy as screwing in a light bulb

## GIVES A BEAUTIFUL FINISHED LOOK

- ▶ Quickest and easiest LED downlight replacement - Installs in seconds
- ▶ PATENTED SPRING LOADED Shaft automatically snaps up tight to ceiling
- ▶ Installs over existing trim (4, 5, or 6" cans)
- ▶ PATENTED Air Flow Cooling
  - Stops premature LED failure
  - LEDs stay cooler, last far longer
- ▶ Thermo-Block Heat Shield – blocks hot attic air (Patent Pending)
- ▶ 50% More Light Area Coverage (5 1/2" Diameter Lens)
- ▶ 10 Year Limited Warranty
- ▶ Flicker Free
- ▶ 72 LED Chips for an Even Lighting Spread with No Hot Spots



**NEW  
PATENTED  
TECHNOLOGY**  
Stops Premature LED Failure

# COOLED<sup>TM</sup> LITE

LED Downlight  
Bulb Replacement

**10  
YEAR  
WARRANTY**

**100W**  
EQUIVALENT  
**12W LED**  
3000K  
WARM WHITE

Gives a beautiful finished look  
*"As easy as screwing in a light bulb"*





### Facts about the CooLEDlite

CooLEDlite™ is the best LED light for any ceiling light application.

- CooLEDlite has over 50% more light coverage than other ceiling lights of the same style.
- The patented air flow technology will keep your LED lights brighter and lasting longer than other manufacturing's LED ceiling lights.
- We are so confident that our lights will outlast others that we give you the only 10 Year Limited Warranty in the market for this type of LED light.



<b>PRODUCT SPECIFICATIONS</b>		
<b>MODEL:</b>	<b>CLD-010930</b>	<b>CLD-012930</b>
Wattage:	10W	12W
Estimated lumens:	750	900
Estimated Efficacy :	75 Lumens/W	75 Lumens/W
Color Temperature:	3000K	3000K
CRI:	90	90
Base Type:	E26	E26
Beam Angle:	108°	108°
Input Voltage:	120V/60Hz	120V/60Hz
Dimmable Range:	10%-100%	10%-100%
Compatible Dimmers:	LUTRON: DV-603PH, TGCL-153PH, CTCL-153PD, D600PH-DK, TG600FR-WH, S-600 LEVITON: 6684,6631,6681	
Power Factor:	>0.95	>0.95
THD:	20%	20%
Shaft Dimensions:	Max: 140mm & Min: 100mm	
Lifetime*:	50,000 hours	50,000 hours
Warranty:	5 years	5 years
Certificate:	ETL & Energy Star	ETL & Energy Star
Operating Temperature:	-20° to +45°	-20° to +45°
Flicker Percentage:	<20%	<20%
<b>PACKAGING/SHIPMENT INFORMATION</b>		
Product N.W.	0.43kg	0.43kg
Estimated Box G.W.:	0.59kg	0.59kg
Estimated Carton G.W.:	4.5kgs	4.5kgs
Estimated Box Size:	305*60*250/mm	305*60*250/mm
Qty per Carton:	6pcs/ctn	6pcs/ctn
Estimated Master Carton Size:	375*320*270/mm	375*320*270/mm
20GP Loading Qty (w/ pallet)	4536 pcs	4536 pcs
20GP Loading Qty (w/ paper slip sheet)	5184 pcs	5184 pcs
40GP Loading Qty (w/ pallet)	9072 pcs	9072 pcs
40GP Loading Qty (w/ paper slip sheet)	10,368 pcs	10,368 pcs

\*Based on IESNA LM80-2008 50,000 hours at 70% lumen maintenance (L70).