

Product Ref	Product_Zone	Product_Type	Prod Dimmable	Light Source_Data_Full	Light Source_Description	Prod Class	Prod IK Rating	Prod Sensor_Description	Prod Voltage
1010	Exterior	Linear vapor tight	0-10V dimmable	60W 6,360Lm 106Lm/W 4,000K	60W (Natural white) SMD 2835	Class 1	IK08	150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.6A max
1022	Exterior	Linear Tri-Proof	0-10V dimmable	45W 4,725Lm 105Lm/W 4,000K	45W (Natural white) SMD 2835	Class 1	IK10	150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.45A max
1025	Interior	Surface mount puff	TRIAC dimmable	16W 1,600Lm 100Lm/W 4,000K	16W (Natural white) SMD 2835	Class 1			120V 50/60Hz 0.18A max
1034	Exterior	Eyelid bulkhead	TRIAC dimmable	18W 1,440Lm 80Lm/W 4,000K	18W (Natural white) SMD 2835	Class 1	IK10		120V 50/60Hz 0.2A max
1052	Exterior	Decorative lantern	Non-dimmable	7W 560Lm 80Lm/W 3,000K	7W (Warm white) SMD 5630	Class 1	IK10		100V - 277V 50/60Hz 0.1A max
1057	Exterior	Decorative lantern	Non-dimmable	7W 560Lm 80Lm/W 3,000K	7W (Warm white) SMD 2835	Class 1	IK10		100V - 277V 50/60Hz 0.1A max
1064	Exterior	Square canopy light	Non-dimmable	50W 5,725Lm 115Lm/W 5,000K	50W (Daylight white) SMD 3030	Class 1	IK07		120V - 277V 50/60Hz 0.5A max
1065	Exterior	Square canopy light	Non-dimmable	75W 9,108Lm 121Lm/W 5,000K	75W (Daylight white) SMD 3030	Class 1	IK07		120V - 277V 50/60Hz 0.75A max
1068	Exterior	Round canopy light	Non-dimmable	50W 5,955Lm 119Lm/W 5,000K	50W (Daylight white) SMD 3030	Class 1	IK07		120V - 277V 50/60Hz 0.5A max
1069	Exterior	Round canopy light	Non-dimmable	75W 9,108Lm 121Lm/W 5,000K	75W (Daylight white) SMD 3030	Class 1	IK07		120V - 277V 50/60Hz 0.75A max
1071	Exterior	Round canopy light	Non-dimmable	120W 13,450Lm 112Lm/W 5,000K	120W (Daylight white) SMD 3030	Class 1	IK07		120V - 277V 50/60Hz 1.2A max
1105	Exterior	Plain bulkhead	0-10V dimmable	24W 2,592Lm 108Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10		120V - 277V 50/60Hz 0.25A max
1106	Exterior	Eyelid bulkhead	0-10V dimmable	24W 2,256Lm 94Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10		120V - 277V 50/60Hz 0.25A max
1107	Exterior	Plain bulkhead	0-10V dimmable	24W 2,592Lm 108Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10	150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.25A max
1108	Exterior	Eyelid bulkhead	0-10V dimmable	24W 2,256Lm 94Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10	150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.25A max
1110	Exterior	Eyelid bulkhead	0-10V dimmable	24W 2,256Lm 94Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10		120V - 277V 50/60Hz 0.25A max
1111	Exterior	Plain bulkhead	0-10V dimmable	24W 2,592Lm 108Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10	150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.25A max
1120	Exterior	Eyelid bulkhead	0-10V dimmable	24W 2,256Lm 94Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10	150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.25A max
1159	Exterior	Door wall pack	Non-dimmable	18W 2,000Lm 111Lm/W 5,000K	18W (Daylight white) SMD 3030	Class 1	IK07		120V - 277V 50/60Hz 0.19A max
1161	Exterior	Door wall pack	Non-dimmable	18W 2,000Lm 111Lm/W 5,000K	18W (Daylight white) SMD 3030	Class 1	IK07	20 Lux On 20 Lux Off	120V - 277V 50/60Hz 0.19A max
1162	Exterior	Door wall pack	Non-dimmable	26W 2,860Lm 110Lm/W 5,000K	26W (Daylight white) SMD 3030	Class 1	IK07	20 Lux On 20 Lux Off	120V - 277V 50/60Hz 0.27A max
1165	Exterior	Deck landscape	Non-dimmable	10 x 0.72W 280Lm 39Lm/W 3,000K	10 x 0.72W (Warm white) SMD 2835	Class 2	IK02		100V - 240V 50/60Hz 0.3A max
1174	Exterior	Deck landscape	Non-dimmable	10 x 0.5W 80Lm 16Lm/W 5,000K	10 x 0.5W (Daylight white) SMD 2835	Class 2	IK02		100V - 240V 50/60Hz 0.3A max
1175	Exterior	Deck landscape	RF controller included	10 x 0.5W RGB	10 x 0.5W (RGB) SMD 5050	Class 2	IK02		100V - 240V 50/60Hz 0.3A max
1183	Exterior	Plain step light	RF controller included	5.4W RGB	5.4W (RGB) SMD 5050	Class 2	IK02		100V - 240V 50/60Hz 0.3A max
1184	Exterior	Plain step light	RF controller included	5.4W RGB	5.4W (RGB) SMD 5050	Class 2	IK02		100V - 240V 50/60Hz 0.3A max
1198	Exterior	Grill bulkhead	0-10V dimmable	24W 2,328Lm 97Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10		120V - 277V 50/60Hz 0.25A max
1199	Exterior	Grill bulkhead	0-10V dimmable	24W 2,328Lm 97Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10	150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.25A max
1200	Exterior	Grill bulkhead	0-10V dimmable	24W 2,328Lm 97Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10		120V - 277V 50/60Hz 0.25A max
1201	Exterior	Grill bulkhead	0-10V dimmable	24W 2,328Lm 97Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10	150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.25A max
1205	Exterior	Grill bulkhead	0-10V dimmable	24W 2,328Lm 97Lm/W 4,000K	24W (Natural white) SMD 2835	Class 1	IK10	150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.25A max
1225	Exterior	Spot landscape	Non-dimmable	5W 500Lm 100Lm/W 5,000K	5W (Daylight white) COB	Class 2			100V - 240V 50/60Hz 0.3A max
1227	Exterior	Spot landscape	Non-dimmable	5W 500Lm 100Lm/W 5,000K	5W (Daylight white) COB	Class 2			100V - 240V 50/60Hz 0.3A max
1228	Exterior	Spot landscape	RF controller included	3W RGB	3W (RGB) SMD 5050	Class 2			100V - 240V 50/60Hz 0.3A max
1229	Exterior	Spot landscape	RF controller included	3W RGB	3W (RGB) SMD 5050	Class 2			100V - 240V 50/60Hz 0.3A max
1230	Exterior	Spot landscape	RF controller included	3W RGB	3W (RGB) SMD 5050	Class 2			100V - 240V 50/60Hz 0.3A max
1233	Interior	Linear wraparound	0-10V dimmable	40W 4,200Lm 105Lm/W 4,000K	40W (Natural white) SMD 2835	Class 1		150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.4A max
1235	Interior	Linear wraparound	0-10V dimmable	52W 5,460Lm 105Lm/W 4,000K	52W (Natural white) SMD 2835	Class 1		150° detection angle 33' (10m) distance	120V - 277V 50/60Hz 0.55A max
1262	Exterior	Deck landscape	Non-dimmable	10 x 0.5W 80Lm 16Lm/W 3,000K	10 x 0.5W (Warm white) SMD 2835	Class 2	IK02		100V - 240V 50/60Hz 0.3A max
1263	Exterior	Spot landscape	Non-dimmable	5W 500Lm 100Lm/W 3,000K	5W (Warm white) COB	Class 2			100V - 240V 50/60Hz 0.3A max
1264	Exterior	Spot landscape	Non-dimmable	5W 500Lm 100Lm/W 3,000K	5W (Warm white) COB	Class 2			100V - 240V 50/60Hz 0.3A max
1265	Exterior	Spot landscape	Non-dimmable	5W 500Lm 100Lm/W 3,000K	5W (Warm white) COB	Class 2			100V - 240V 50/60Hz 0.3A max